

## SUN-BATT-10.65

Self consumption  
Energy independence



### MORE USABLE ENERGY

100% Depth of Discharge



### FLEXIBLE INVESTMENT

Scalable from 10.65 to 85.2 kWh



### SAFE & RELIABLE

Premium Lithium Iron Phosphate(LFP)  
6000 cycles



### EASY INSTALLATION

Floor Stand or Wall Mounted



### HIGH ENERGY DENSITY

Proprietary CTP Technology



### PERFECT COMPATIBILITY

Compatible with Major PCS Brand

## SUN-BATT-10.65 Technical Specification

Performance	
Nominal Voltage	51.2 Vdc
Nominal Capacity	208Ah
Battery Energy <sup>1</sup>	10650 Wh
Charge Voltage	55.68~56.16Vdc
Discharge Voltage	45.6~56.16 Vdc
Nominal Charge/Discharge Current	100A
Nominal Charge/Discharge Power	5000W
Max Charge / Discharge Current	200A
Max Charge / Discharge Power	10000W
Short Circuit Current	540A
Communication	
Display	SOC status indicator, LED indicator
Communication	RS232、RS485、CAN
General Specification	
Dimension( W×D×H mm )	550×160×836mm
Weight (Kg)	90kg
Installation	Floor stand or Wall mounted
Working Temperature <sup>2</sup>	-20°C ~ 60°C
Storage Temperature	≤25°C,12 months; ≤35°C,6 months; ≤45°C,3 months
Operating / Storage / humidity	≤ 95%RH
Max Operating Altitude	≤2000m
IP Rating	IP20
Cell Technology	LiFePO <sub>4</sub> , Lithium Iron Phosphate
Cycle life <sup>3</sup>	6000 Cycles @ 80% DOD / 25°C / 0.5C, 60% EOL
Scalability	Max 8 batteries in parallel
Standard Compliance	
Certification	PACK: UN38.3、IEC62619、IEC61000 CELL: UN38.3、IEC62619、UL 1642、JET (more available upon request)
Ordering and Deliverable Part	
Product ordering part	SUN-BATT-10.65 Battery SUN-BATT-10.65 Parallel cable SUN-BATT-10.65 to PCS cable

1. Test conditions: 100% depth of discharge (DoD), 0.2C rate charge & discharge at 25°C

2. Charge/discharge derating occurs when the operating temperature from -10°C to 5 °C.& 45 °C to 55 °C.

3. Condition apply. Refer to SUN-BATT-10.65 Warranty Letter