

Hisense HVAC

OFFICIAL PARTNER



Aeolus Fixed Speed

OF
YOUR
HOME

#hisenseheartofthehome



AI Smart



Fast
Cooling



Dimmer



High Density
Filter



Super Mode



Super Quiet
Mode



Self-Diagnosis
Protection



Auto Restart



8°C Heating



Non-Inverter Type		AS-09HW4SYRCK00 Heat pump	AS-12HW4SVRCK04 Heat pump	AS-18HW4SXSK01 Heat pump	AS-22HW4SBTCK00 Heat pump
RATINGS					
Cooling Capacity	W	2500	3200	5000	6100
Heating Capacity	W	2600	3300	5200	6250
Power Input-Cooling	W	810	1050	1625	2000
Power Input-Heating	W	695	960	1510	1825
Moisture Removal	L/H.r	-	-	-	-
Air Circulation	CMH Max	600	580	950	1100
EER for Cooling	W/W	3.09	3.05	3.08	3.05
COP for Heating	W/W	3.74	3.44	3.44	3.42
Energy Consumption	kWh / year	405	525	812.5	1000
Energy Class for SA	Cooling	B	B	B	B
Energy Class for SA	Heating	A++	A+	A+	A+
Refrigerant		R410A	R410A	R410A	R410A
Refrigerant Volume	g	620	700	1250	1430
Indoor Unit Noise Level	High (dB (A)) Low (dB (A))	38 -	39 -	43 -	45 -
Outdoor Unit Noise Level	dB (A)	51	53	54	57
POWER SUPPLY					
Voltage, Frequency, Phase		220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V~,50Hz,1P	220-240V/50Hz
Rated Current	Cooling (A) Heating (A)	3,8 3,3	5,1 4,7	7,3 6,8	8,9 8,2
LRA	A	20	25	41	45
CONNECTING PIPE DIAMETER					
Liquid Pipe	inch	1/4	1/4	1/4	3/8
Gas Pipe	inch	3/8	3/8	1/2	5/8
Maximum Connection Pipe Length	m	15	15	15	15
Maximum Height Difference	m	5	5	5	5
OTHER (VQ PANEL)					
Net Dimensions WxHxD (mm)	Indoor Unit Outdoor Unit	790x197x255 660x482x240	790x197x255 715x482x240	890x220x300 810x585x280	998x225x325 860x650x310
Net Weight (kg)	Indoor Unit Outdoor Unit	7,5 25	7,5 26	10 41	12,5 42,5
Packing Dimensions WxHxD (mm)	Indoor Unit Outdoor Unit	850x260x320 780x530x345	850x260x320 830x530x345	960x300x365 940x630x385	1060x315x390 995x720x420
Gross Weight (kg)	Indoor Unit Outdoor Unit	9 27	9 28,5	12 45	15 46,5


Fast Cooling

By pressing the "SUPER" button, the air conditioner is not affected by the ambient temperature, and always runs at the maximum power and air volume to quickly reduce the indoor temperature.



4-IN-1 Filter

Achieve the combined effect of multiple single filters like dust removal, deodorization, PM2.5 removal, sterilization, virus removal, and fragrance room.



Easy Maintenance

Unique IDU structure, no need to move evaporator when disassembling indoor electromechanical machine, can replace PCB, cross flow fan motor quickly and easily.



Anti-corrosive Golden Fin

Golden fin, which corrosion protection level is significantly 3 to 4 times better than normal fin, can effectively withstand the salty air, rain and other corrosive elements.

