

comfee' Ambient

Inverter Midwall Split Air Conditioner



- **Inverter Energy Saving** - Reduces energy consumption while maintaining comfort.
- **WI-FI compatible** (optional extra) - Control your unit from your smartphone.
- **R32 Refrigerant** – Environmentally friendly refrigerant.
- **Heating and Cooling** – Year-round comfort in every season.
- **Fast Cooling** - Quickly reaches your desired temperature.
- **Sleep Mode** – Adjusts temperature for a comfortable night's sleep.
- **Clean Mode** – Keeps the indoor unit clean and fresh.
- **LED Display** – Temperature display that can be switched on or off.
- **Wired Controller compatible** (additional extra)

Comfee Inverter

Comfee ...is how I feel!



Stay comfortable all year with the Comfee Ambient Inverter Midwall Air Conditioner. With heating and cooling, it helps keep your space at a steady, comfortable temperature while using energy efficiently. Add the optional Wi-Fi dongle, sold separately, for convenient control from your smartphone. Each unit includes 2m of copper piping. Enjoy added peace of mind with a 1-year warranty on the unit, a 3-year warranty on the compressor and support from Fourways Group's nationwide branch network.

Indoor			FCMI-L-09	FCMI-L-12	FCMI-L-18	FCMI-L-24
Power Supply		V-Ph-Hz	220_240V_1Ph,50HZ	220_240V_1Ph,50HZ	220_230V_1Ph,60HZ	220_230V_1Ph,60H
Cooling (Standard conditions)	Capacity	Btu/h	9000	12000	18000	24000
	Input	W	876	1168	1696	2262
	Current	A	3.81	5.08	7.38	9.83
	EER	W/W	3.01	3.01	3.11	3.11
	Cooling Class		B	B	B	B
Heating (Standard conditions)	Capacity	Btu/h	9500	12000	18500	24000
	Input	W	771	974	1580	1911
	Current	A	3.6	4.46	7	8.3
	COP	W/W	3.61	3.61	3.55	3.68
	Heating Class		A++	A++	A+	A++
Rated Power Input		W	2030	2300	2500	2840
Rated Current		A	9.0	10.5	13.5	13
Indoor air flow (Hi/Mi/Lo)		L/s	510/360/285	550/400/250	850/650/550	1150/840/670
Indoor noise level (H/M/Lo)		dB(A)	36/30/22	36/32/20.5	43.5/41.5/33	45/39.5/36
Indoor unit	Dimentoins (W*D*H)	mm	723x199x286	813x201x289	975x218x308	1055x231x330
	Packing (W*D*H)	mm	780x270x365	870x270x365	1035x295x385	1130x405x310
	Net/Gross weight	kg	7.5/9.6	8.1/10.5	10.0/13.2	12/15.5
Outdoor			FCMI-L-09X	FCMI-L-12X	FCMI-L-18X	FCMI-L-24X
Outdoor air flow		L/s	1300	1800	2100	2300
Outdoor noise level		dB(A)	51	55	57	57
Outdoor unit	Dimentions (W*D*H)	mm	668x252x469	720x270x495	765x303x555	805x330x554
	Packing (W*D*H)	mm	765x270x515	835x300x540	887x337x610	915x370x615
	Net/Gross Weight	kg	17.9/19.5	19.9/21.8	24.4/26.7	31.8/34.2
Refrigerant type		kg	R32/0.45	R32/0.53	R32/0.9	R32/1.1
Design pressure		MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)
	Max, refrigerant pipe lenght	m	25	35	30	30
	Max, difference in level	m	10	10	20	20
Connection wiring			1.5x4//	1.5x4//	16x4//	16x4//
Plug type			1.5x3VDE	1.5x3/VDE	//no-plug	//no-plug
Thermostat type			(IR Remote Control)	(IR Remote Control)	(IR Remote Control)	(IR Remote Control)
Room temperature	Indoor (cooling/heating)	℃	16~32/0~30	16~32/0~30	16~32/0~30	16~32/0~30
	Outdoor (cooling/heating)	℃	-15~50/-15~24	-15~50/-15~24	0~50/-15~24	0~50/-15~24

2m Copper Pipe
Convenient & included.

1 year warranty
on the unit.

3 year warranty
on the compressor.

*** ADDITIONAL EXTRAS**
· Wi-Fi Dongle: Model Code: 17310900003721
· Wired remote : Model Code 17317100002997

Comfee reserves the right to discontinue or change specifications at any time without notice and without incurring obligation. E&OE.

Comfee