

comfee' Ambient

Non-Inverter Midwall Split Air Conditioner



- **R32 Refrigerant** – Environmentally friendly refrigerant.
- **Heating and Cooling** – Year-round comfort in every season.
- **Fast Cooling** – Quickly reaches your desired temperature.
- **Sleep Mode** – Adjusts temperature for a comfortable night's sleep.
- **Clean Mode** - Keeps the indoor unit clean and fresh.
- **LED Display** – Temperature display that can be switched on or off.

Comfee Non-Inverter

The Comfee Ambient Non-Inverter Midwall Air Conditioner delivers reliable heating and cooling for year-round comfort. Practical and easy to use, also includes 2m of copper piping. Backed by Fourways Group's nationwide branch network, it comes with a 1-year warranty on the unit and a 3-year warranty on the compressor, giving you added peace of mind.

Comfee ...is how I feel!



Indoor			FCMF-L-09	FCMF-L-12	FCMF-L-18	FCMF-L-24
Power Supply		V-Ph-Hz	220_240V_1Ph,50HZ			
Cooling (Standard conditions)	Capacity	Btu/h	9000	12000	18000	24000
	Input	W	821	1095	1750	2190
	Current	A	3.9	5.5	8.0	9.6
	EER	W/W	3,01	3,01	3,01	3,21
	Cooling Class		B	B	B	A
Heating (Standard conditions)	Capacity	Btu/h	9500	12700	19000	25000
	Input	W	771	1031	1543	2030
	Current	A	3.6	4.9	7.0	8.8
	COP	W/W	3,38	3,56	3,46	3,61
	Heating Class		A	A+	A+	A++
Rated Power Input		W	1300	1600	2520	3100
Rated Current		A	7.5	9.5	14.0	16.3
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY
Indoor air flow (H/M/Lo)		L/s	554/490/343	560/490/360	850/710/600	1250/1090/870
Indoor noise level (H/M/Lo)		dB(A)	40.5/37/26	40.5/36/27.0	43/37/32	46/42/36
Indoor unit	Dimentoins (W*D*H)	mm	723x199x286	813x201x289	975x218x308	1055x231x330
	Packing (W*D*H)	mm	780x270x365	870x270x365	1035x295x385	1130x405x310
	Net/Gross weight	kg	7.6/9.9	8.5/10.8	10.6/13.6	12.4/15.9
Outdoor			FCMF-L-09X	FCMF-L-12X	FCMF-L-18X	FCMF-L-24X
Outdoor air flow		L/s	1800	1800	2100	4200
Outdoor noise level		dB(A)	52.5	54.0	57	61.5
Outdoor unit	Dimentions (W*D*H)	mm	720x270x495	720x270x495	765x303x555	890x342x673
	Packing (W*D*H)	mm	835x300x540	835x300x540	887x337x610	995x398x740
	Net/Gross Weight	kg	25.1/26.9	25.5/27.3	33.4/35.6	48.1/51.1
Refrigerant type		kg	R32/0.48	R32/0.48	R32/0.85	R32/1.2
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)
	Max, refrigerant pipe lenght	m	20	20	25	25
	Max, difference in level	m	8	8	10	10
Connection wiring			1.5x3/0.75x2	1.5x3/0.75x2	2.5x3/0.75x2	2.5x3/0.75x2
Plug type			1.5x3VDE	1.5x3VDE	2.5x3/no-plug	2.5x3/no-plug
Thermostat type			(IR Remote Control)	(IR Remote Control)	(IR Remote Control)	(IR Remote Control)
Room temperature	Indoor (cooling/heating)	℃	16~32/0~30	16~32/0~30	16~32/0~30	16~32/0~30
	Outdoor (cooling/heating)	℃	18~43/-7~24	18~43/-7~24	18~43/-7~24	18~43/-7~24

Comfee reserves the right to discontinue or change specifications at any time without notice and without incurring obligation. E&OE.

2m Copper Pipe
Convenient & included.

1 year warranty
on the unit.

3 year warranty
on the compressor.

Comfee